



Bearing No. BT4B 334081/HA4

Size	1264x896.903x766 mm
Bore Diameter	1264 mm
Outer Diameter	896,903 mm
Width	766 mm
d	896.903 mm
D	1264 mm
B	766 mm
T	680 mm
$r_{1,2}$ - min.	12.7 mm
$r_{3,4}$ - min.	3.3 mm
Basic dynamic load rating - C	22900 kN
Basic static load rating - C_0	64000 kN
Fatigue load limit - P_u	3800 kN
Comparative radial load rating - C_F	6100 kN
Comparative axial load rating - C_{Fa}	1120 kN
Thrust factor - K	1.57
Calculation factor - e	0.37
Calculation factor - Y_1	1.8
Calculation factor - Y_2	2.7
Calculation factor - Y_0	1.8
Mass bearing	3100 kg
Design variant/feature	TQIT.1
d_1 ?	1055 mm
D_1 ?	1197 mm
$r_{1,2}$ min.	12.7 mm
$r_{3,4}$ min.	3.3 mm

Basic dynamic load rating C	22900 kN
Basic static load rating C_0	64000 kN
Fatigue load limit P_u	3800 kN
Comparative radial load rating C_F	6100 kN
Comparative axial load rating C_{Fa}	1120 kN
Thrust factor K	1.57
Calculation factor e	0.37
Calculation factor Y_1	1.8
Calculation factor Y_2	2.7
Calculation factor Y_0	1.8